

SLR200 SERIES

SELF-LEVELING ROTARY LASERS



Versatility and Productivity in
General Construction Applications



SitePro[™]


SLR200HV HORIZONTAL & VERTICAL ROTARY LASER



SLR200H HORIZONTAL ROTARY LASER



Features



- Horizontal and vertical electronic self-leveling for precise leveling applications, ideal for both indoor and outdoor use
- Leveling accuracy up to 1/8-in at 100-ft (3mm at 30m) with working range up to 1600-ft (500m) diameter
- Self leveling range up to +/- 5° that can sense and indicate out-of-level conditions
- Manual Mode allows laser to tilted for simple slope applications
- Smart H.I. Alert System alerts user when laser has been disturbed
- Vertical Laydown Positioning for vertical alignment and squaring to ensure that walls or partitions are precisely aligned
- Variable rotation speeds for a wide variety of jobsite visibility settings: 0, 60, 300 and 600RPM
- Scan Angles: 10°, 45°, 90°, 180°; for maximum visibility
- Visible 90-degree layout beams (both up and down plumb) for alignment and squaring to ensure that walls or partitions are precisely aligned
- Clock-wise and counter-clock-wise beam positioning
- Dual Manual grade matching up to 8.77% in both axes
- Enclosed Rotor Housing keeps laser safe from tough jobsite conditions
- Windy Mode Feature allows laser to level at jobsites with high winds or vibrations

Model Package

Package Content

27-SLR200HV

Rotary Laser, RC28 Remote, Glasses, Magnetic Target, Multi-Mount, RD200 Laser Detector w/Clamp, NiMH Rechargeable Battery Pack, Carrying Case, User Manual

Features



- Horizontal self-leveling for precise outdoor leveling applications
- Leveling accuracy up to 1/8-in at 100-ft (3mm at 30m) with working range up to 1600-ft (500m) diameter
- Self leveling range up to +/- 5° that can sense and indicate out-of-level conditions
- Manual Mode allows laser to tilt for simple slope applications
- Smart H.I. Alert System alerts user when laser has been moved
- Variable rotation speeds for a wide variety of jobsite visibility settings: 0, 60, 300 and 600RPM
- Dual Manual grade matching up to 8.77% in both axes
- Enclosed rotor housing keeps laser safe from the elements or tough jobsite conditions

Model Package

Package Content

27-SLR200H

Rotary Laser, RD200 Laser Detector w/Clamp, Carrying Case, User Manual

27-SLR200HU

Rotary Laser, RD200 Laser Detector w/Clamp, NiMH Rechargeable Battery Pack, Carrying Case, User Manual

Vertical Laydown Positioning for alignment and squaring to ensure that walls or partitions are precisely aligned.



Specifications

	SLR200HV	SLR200H
Horizontal Accuracy @ 100-ft (30m)	1/8-in (3mm)	1/8-in (3mm)
Range with Detector (Diameter)	1600-ft (500m)	1600-ft (500m)
Interior Range (Diameter)	320-ft (98m)	n/a
Leveling Type (Degrees)	Electronic (±5°)	Electronic (±5°)
Beam Rating	Class 3R, 635nm	Class 2M, 650nm
Vertical Self-Leveling @ 100-ft (30m)	1/8-in (3mm)	n/a
Slope/Grade Capability	Dual (±8.77%)	Dual (±8.77%)
Battery Type	4-C Cell, NiMH Rechargeable	4-C Cell, NiMH Rechargeable
Water/Dust Protection	IP55	IP55

